



DATA SHEET

KOPRO LED extrusion – article number B6367ANODA

Product characteristics

The angular extrusion is made from high quality, double-anodized aluminum, designed for a maximum of two flexible or rigid LED strips that are 8 - 10 mm wide. The frosted cover options are: KOPRO P, KOPRO K or KOPRO L which are made of polycarbonate.

Additional accessories for the extrusion are polypropylene end caps.

The extrusion can be mounted to surfaces with the use of mounting glue or screws which guarantee easy and secure mounting of the extrusion to the desired surface. Installation of the extrusion in drywall is performed using special GP Mounting Springs. ZM connectors are used for straight and angle connections of KLUS profiles fitted with a small fastener and to stabilize the ends of the profiles mounted in lines.

All optional accessories are described on our website, www.KlusDesign.com.

Applications

The extrusion with the LED light source is ideal for creating light illuminations indoors. The possibility of getting a single line of light, thanks to the frosted cover (KOPRO L or KOPRO K) makes this extrusion fit all types of arrangements very well. Due to the possibility of installing two strips inside the extrusion it can also be used as a primary energy-efficient light source.

Products related to the Extrusion



cover type KOPRO P
frosted (17091)



cover type KOPRO L
frosted (17092)



cover type KOPRO K
frosted (17093)



end cap KOPRO P
without hole (24117)



end cap KOPRO L
without hole (24116)





end cap KOPRO K
without hole (24115)

Technical specification

Ingress Protection Rating IP 20

Product Number B6367_1 (39.4")
B6367_2 (78.7")

Material body – aluminum, cover – polycarbonate (PC), end cap – polypropylene (PP), spring, ZM connector – steel



www.KlusDesign.com

We reserve the right to change and modify our products

Vero Beach, FL 32962 / United States / Customer Service: sophia@klusdesign.com / (Ph.) 772 321 2260, 772 569 6655