

V	W	A	Price	SKU	Volts		Certification	Class	Breaker			Size				Housing
					AC In	DC Out			Prim.	Sec.	Reset	Height	Width	Depth	Pounds	
12V	20w	1.67a	\$74	ZRK-20-12VDC	120v	12v	ETL (US, C)	2	✓	✓	Auto	S 7 3/8"	2 1/8"	1 5/8"	1.6	In & Outdoors
	40w	3.33a	\$79	ZRK-40-12VDC	120v	12v	ETL (US, C)	2	✓	✓	Auto	S 7 3/8"	2 1/8"	1 5/8"	2.3	In & Outdoors
	60w	5.00a	\$87	ZRK-60-12VDC	120v	12v	ETL (US, C)	2	✓	✓	Manual	M 8 1/8"	4"	1 5/8"	3.8	In & Outdoors
	100w	8.33a	\$105	ZRK-100-12VDC	120v	12v	ETL (US, C)		✓	✓	Manual	M 8 1/8"	4"	1 5/8"	4.2	In & Outdoors
	150w	12.50a	\$124	ZRK-150-12VDC	120v	12v	ETL (US, C)		✓	✓	Manual	L 8"	4 1/4"	3 1/2"	7.4	In & Outdoors
	200w	16.67a	\$155	ZRK-200-12VDC	120v	12v	ETL (US, C)		✓	✓	Manual	L 8"	4 1/4"	3 1/2"	7.4	In & Outdoors
	250w	20.83a	\$175	ZRK-250-12VDC	120v	12v	ETL (US, C)		✓	✓	Manual	L 8"	4 1/4"	3 1/2"	8.3	In & Outdoors
	300w	25.00a	\$195	ZRK-300-12VDC	120v	12v	ETL (US, C)		✓	✓	Manual	L 8"	4 1/4"	3 1/2"	8.3	In & Outdoors
24V	20w	.83a	\$74	ZRK-20-24VDC	120v	24v	ETL (US, C)	2	✓	✓	Auto	S 7 3/8"	2 1/8"	1 5/8"	1.6	In & Outdoors
	40w	1.67a	\$79	ZRK-40-24VDC	120v	24v	ETL (US, C)	2	✓	✓	Auto	S 7 3/8"	2 1/8"	1 5/8"	2.1	In & Outdoors
	50w	2.08a	\$87	ZRK-50-24VDC	120v	24v	ETL (US, C)	2	✓	✓	Auto	S 7 3/8"	2 1/8"	1 5/8"	2.1	In & Outdoors
	75w	3.13a	\$99	ZRK-75-24VDC	120v	24v	ETL (US, C)	2	✓	✓	Manual	M 8 1/8"	4"	1 5/8"	3.9	In & Outdoors
	96w	4.00a	\$105	ZRK-100-24VDC	120v	24v	ETL (US, C)	2	✓	✓	Manual	M 8 1/8"	4"	1 5/8"	4.3	In & Outdoors
	150w	6.25a	\$124	ZRK-150-24VDC	120v	24v	ETL (US, C)		✓	✓	Manual	L 8"	4 1/4"	3 1/2"	7.7	In & Outdoors
	200w	8.33a	\$155	ZRK-200-24VDC	120v	24v	ETL (US, C)		✓	✓	Manual	L 8"	4 1/4"	3 1/2"	7.7	In & Outdoors
	250w	10.42a	\$175	ZRK-250-24VDC	120v	24v	ETL (US, C)		✓	✓	Manual	L 8"	4 1/4"	3 1/2"	8.4	In & Outdoors
	300w	12.50a	\$195	ZRK-300-24VDC	120v	24v	ETL (US, C)		✓	✓	Manual	L 8"	4 1/4"	3 1/2"	8.4	In & Outdoors

- Zurik Drivers are made in the USA and come with a 10-year warranty
- Must to be installed in a well-ventilated area which has free flow of air
- For optimum performance, load the unit between 50-80% of wattage rating

- Not compatible with the Hybrid or RGB Series Strip Lights
- Must be installed vertically to ensure protection against weather
- These LED Dimmable Drivers are ONLY to be used with the compatible magnetic low voltage (MLV) Lutron wall switches found on our website